

DATE:	PROJECT:	TYPE:
-------	----------	-------

CATALOG NUMBER LOGIC:

**CATALOG NUMBER LOGIC**

Example: PTR - 4 - 26 - AR - LED - RM - e66 - SP - A9 - VER - 12 - 11 - C

**MATERIAL**

Aluminum

**SERIES**

PTR - Palm Tree Ring

**FIXTURE QUANTITY**

2 - 2 @ 180°      4 - 4 @ 90°

3 - 3 @ 120°      6 - 6 @ 60°

**STRAP SIZES**

16 - 16" min. to 22" max. tree diameter

21 - 21" min. to 27" max. tree diameter

26 - 26" min. to 32" max. tree diameter

31 - 31" min. to 38" max. tree diameter

**FIXTURE**

AR - ArtiStar

**SOURCE**

LED - with Integral Driver\*

**HOUSING**

RM - Remote Transformer

**LED TYPE**

e64 - 7W LED/2700K      e79 - 7W LED/2700K 90CRI

e65 - 7W LED/3000K      e80 - 7W LED/3000K 90CRI

e66 - 7W LED/4000K      e81 - 7W LED/3500K 80CRI

e74 - 7W LED/Amber

**OPTICS**

NSP - Narrow Spot (17°)      MFL - Medium Flood (28°)

SP - Spot (21°)      WFL - Wide Flood (60°)

**ADJUST-E-LUME OUTPUT INTENSITY\*\***

A9 (Standard), A8, A7, A6, A5, A4, A3, A2, A1

**FINISH (See page 2 for full-color swatches)**

Standard Finishes (BZP, BZW, BLP, BLW, WHP, WHW, SAP, VER)

Premium Finish (ABP, AMG, AQW, BCM, BGE, BPP, CAP, CMG, CRM, HUG, NBP, OCP, RMG, SDS, SMG, TXF, WCP, WIR)

Also available in RAL Finishes

**LENS TYPE**

12 - Soft Focus      13 - Rectilinear

**SHIELDING**

11 - Honeycomb Baffle (per fixture)

**CAP STYLE**

A - 45° (per fixture)

B - 90° (per fixture)

C - Flush

F - 90° with Flush Lens (per fixture)


\*Designed for use with 12 VAC. LED transformer.

\*\*Please see Adjust-e-Lume photometry to determine desired intensity.

DATE:

PROJECT:


TYPE:



**STANDARD FINISHES**




**PREMIUM FINISHES**



[Click Here](#) to view larger, full-color swatches of all available finishes on our website.

DATE:	PROJECT:	TYPE:
-------	----------	-------

ACCESSORIES (Configure separately)



TR Series

## SPECIFICATIONS

ELECTRICAL	WATTAGE	7W LED
	ADJUST-E-LUME	Integral electronics allows dynamic lumen response at the individual fixture. Indexed (100% to 25% nom.) lumen output. Maintains output at desired level or may be changed as conditions require. Specify factory preset output intensity.
	WIRING	Fixture factory pre-wired with SJEOOW,16/2GA,105C,300V. Nylon Cord Grip for secondary wiring from power supply. (Secondary wiring by Others.) Min. Cable Dia .230" Max. Cable Dia .546"
	REMOTE TRANSFORMER	For use with 12VAC remote transformer or magnetic transformers only. B-K Lighting cannot guarantee performance with third party manufacturers' transformers.
PHYSICAL	MATERIALS	Palm Tree Ring - 1/8" thick AISI 304 stainless steel. Fixture - copper-free aluminum (6061-T6).
	BODY	Unibody design is fully machined from solid billet and provides enclosed, water-proof wireway and integral heat sink for maximum component life. Integral knuckle for maximum mechanical strength. High temperature, silicone 'O' Ring provides water-tight seal.
	KNUCKLE	Aim & Lock knuckle is integral to the body and machined from solid billet. It features an interior, machined taper and a second, reverse angle taper. The resultant mechanical taper-lock allows a full 180° vertical adjustment without the use of aim-limiting serrated teeth. High temperature, silicone 'O' Ring provides water-tight seal and compressive resistance to maintain fixture position. Design withstands 73 lbs. static load prior to movement to ensure decades of optical alignment. Biaxial source control with 360° horizontal rotation in addition to vertical adjustment.
	CAP	Fully machined and accommodates two (2) lens or louver media.
	LENS	Shock-resistant, tempered glass lens is factory adhered to fixture cap and provides hermetically sealed optical compartment.
	LED	Integrated solid state system. High power, forward throw source complies with ANSI C78.377 binning requirements and exceeds ENERGY STAR® lumen maintenance requirements. LM-80 certified components. Integral non-dimming driver. Minimum 50,000 hour rated life at 70% of initial lumens (L70). LED technology provides long life, significant energy reduction and exceptional thermal management.
	DIMMING	Line voltage dimmable via magnetic low voltage dimmer with dedicated neutral conductor. For purposes of dimming: Remote magnetic transformer with LED loads should be loaded to 25% of the transformer VA (watts) rated value.
	OPTICS	Interchangeable, color-coded OPTIKIT modules permit field changes to optical distribution.
	HARDWARE	Tamper-resistant, stainless steel hardware. LOCK aiming screw is black oxide treated for additional corrosion resistance.
	FINISH	StarGuard, our 15-stage chromate-free process cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating and is RoHS compliant. Powder coat or metal finish options available for brass material and metal finish option only for stainless steel material.
	WARRANTY	5-year limited warranty.
CERTIFICATION & LISTING	ITL tested to IESNA LM-79. UL Listed. Certified to CAN/CSA/ANSI Standards. RoHS compliant. Suitable for indoor or outdoor use and in wet locations. IP66 Rated. Made in the USA with sustainable processes.	

**B-K LIGHTING****MADE IN THE USA**

559.438.5800 | INFO@BKLIGHTING.COM | BKLIGHTING.COM

