

DATE:	PROJECT:	TYPE:
-------	----------	-------

CATALOG NUMBER LOGIC:



*Lamp details available on the 3rd page.

**The 360SL cost is already included in the price of UPM, UPM dual, and Power Canopy.

CATALOG NUMBER LOGIC

Example: B - NSII - MR - 359 - SAP - 9 - 11 - 360SL

MATERIAL

(Blank) - Aluminum B - Brass

SERIES

NSII - Nite Star II

SOURCE

MR - MR16 Lamp

LAMP TYPE

0 - MR16 Halogen Lamp (Furnished by others)

MR16 LED (This choice requires lamp number selection)*

FINISH (See page 2 for full-color swatches)

Standard Finishes (BZP, BZW, BLP, BLW, WHP, WHW, SAP, VER)

Premium Finish (ABP, AMG, AQW, BCM, BGE, BPP, CAP, CMG, CRI, CRM, HUG, MDS, NBP, OCP, RMG, SDS, SMG, TXF, WCP, WIR)

Also available in RAL Finishes

Brass Finishes (MAC, POL, MIT)

LENS TYPE

9 - Clear (Standard)

10 - Spread 12 - Soft Focus 13 - Rectilinear

SHIELDING

11 - Honeycomb Baffle



OPTIONS

360SL - Knuckle Mounting System**


DATE:

PROJECT:


TYPE:



Horizontal Rotation
(Optional 360SL™ Knuckle)



180° Vertical Adjustment
(Standard)




F Cap

STANDARD FINISHES




PREMIUM FINISHES



[Click Here](#) to view larger, full-color swatches of all available finishes on our website.

DATE: _____ PROJECT: _____ TYPE: _____


ACCESSORIES (Configure separately)




TR Series




Power Pipe




UPMRM



Power Pipe




Power Canopy




Tree Strap



Stems



Canopies



UPM

SPECIFICATIONS

ELECTRICAL	WATTAGE	
	WIRING	Teflon® coated wire, 18AWG, 600V, 250° C rated and certified to UL 1659 standard. Leads extend 6" beyond knuckle.
	TRANSFORMER	For use with 12 VAC remote transformer.
PHYSICAL	MATERIALS	Furnished in Copper-Free Aluminum (Type 6061-T6), or Brass (Type 360).
	BODY	Fully machined from solid billet. Unibody design provides enclosed, water-proof wireway and heat sink to maximize lamp life. Integral knuckle for maximum mechanical strength. High temperature, silicone 'O' Ring provides watertight seal.
	KNUCKLE	The LOCK™ (Locking 'O' Ring Compression Knuckle) is comprised of two components. The first is integral to the body and features an interior, machined taper. The second is machined from solid billet and features a second, reverse angle taper. The resultant mechanical taper-lock allows a full 180° vertical adjustment without the use of serrated teeth, which inherently limit aiming. High temperature, silicone 'O' Ring provides water-tight seal and compressive resistance to maintain fixture position. Design withstands 73 lb. static load prior to movement to ensure decades of optical alignment. ½" pipe thread for mounting. Optional 360SL™ additionally provides biaxial source control with 360° horizontal rotation in addition to vertical adjustment.
	CAP	Fully machined. 1" deep cutoff with flush mounted lens. Accommodates up to (2) lens or louver media.
	LENS	Shock resistant, tempered, clear glass lens is factory adhered to fixture cap and provides hermetically sealed optical compartment.
	LAMP	For use with 50 watt maximum, bi-pin MR16 lamps. Not for use with IR technology lamps. Halogen source by others. *Except GE Light Q42MR16/C/VNSP9 (EZY).
	SOCKET	Specification grade, ceramic body lamp holder. GU5.3 base. Nickel alloy contacts and heat resistant, spring loaded, stainless steel lamp retaining clips.
	HARDWARE	Tamper-resistant, stainless steel hardware. LOCK™ aiming screw is additionally black oxide treated for additional corrosion resistance.
	FINISH	StarGuard®, our exclusive RoHs compliant, 15 stage chromate-free process cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating. Brass components are available in powder coat or handcrafted metal finish.
	WARRANTY	5 year limited warranty.
CERTIFICATION & LISTING	UL Listed. Certified to CAN/CSA/ANSI Standards. RoHs compliant. Suitable for indoor or outdoor use. Suitable for use in wet locations. Suitable for installation within 4' of the ground. Made in USA.	