

# GARDEN STAR (MR16)

DATE: \_\_\_\_\_ PROJECT: \_\_\_\_\_ TYPE: \_\_\_\_\_

CATALOG NUMBER LOGIC:



## CATALOG NUMBER LOGIC

GR - 502 - BLP - E - 12

## SERIES

GR - Garden Star

## LAMP TYPE

0 - By Others

500 - 7W/15DEG/2700K

501 - 7.5W/25DEG/2700K

502 - 7.5W/35DEG/2700K

503 - 7W/15DEG/3000K

504 - 7.5W/25DEG/3000K

505 - 7.5W/35DEG/3000K

## FINISH (See below for full-color swatches)

Standard Finishes (BZP, BZW, BLP, BLW, WHP, WHW, SAP, VER)

## STYLE


E - Style E

K - Style K


## BASE

12 - 12" with Anchor Base


18 - 18" with Anchor Base




STYLE E



STYLE K



ANCHOR BASE



MOUNTING STAKE

## STANDARD FINISHES



Satin Black (BLP)



Satin Bronze (BZP)



Satin White (WHP)



Satin Aluminum (SAP)



Black Wrinkle (BLW)



Bronze Wrinkle (BZW)



White Wrinkle (WHW)



Verde (VER)

[Click here](#) to view larger color swatches of these finishes on our website



**B-K LIGHTING**

**MADE IN THE USA**

559.438.5800 | [INFO@BKLIGHTING.COM](mailto:INFO@BKLIGHTING.COM) | [BKLIGHTING.COM](http://BKLIGHTING.COM)

# GARDEN STAR (MR16)

DATE:	PROJECT:	TYPE:
-------	----------	-------

ACCESSORIES (Configure separately)

## SPECIFICATIONS

ELECTRICAL	WATTAGE	7W or 7.5W
	SOCKET	Specification grade, ceramic body lamp holder. GU5.3 base. Nickel allow contacts and heat resistant, spring loaded, stainless steel lamp retaining clips.
	WIRING	Teflon® coated wire, 18AWG, 600V, 250° C rated and certified to UL 1659 standard.
	TRANSFORMER	For use with 12 VAC remote transformer.
PHYSICAL	MATERIALS	Furnished in copper-free aluminum (6061-T6).
	BODY	Unibody design is fully machined from solid billet and provides enclosed, water-proof wireway and heat sink to maximize lamp life. High temperature, silicone 'O' Ring provides watertight seal.
	STYLE	Fully machined housing provides wide assortment of visual effects. Style E features a solid clear acrylic rod and Style K features a frosted Pyrex® lens.
	LAMP TYPE	MR16 Green Creative LED Lamp, Title 20 and Title 24, JA8 compliant. Compatible with 20 watt maximum, MR16 lamp.* Not for use with IR technology lamps. Halogen sourced by others. *Except GE Light Q42MR16/C/VNSP9 (EZY).
	INSTALLATION	Fully machined anchor base provides 1/2-14 NPSM threads compatible with provided mounting stake.
	HARDWARE	Tamper-resistant, stainless steel hardware.
	FINISH	StarGuard, our 15-stage chromate-free process cleans and conversion coats aluminum components prior to application of Class 'A' TGIC polyester powder coating and is RoHS compliant.
	WARRANTY	5-year limited warranty.
	CERTIFICATION & LISTING	UL Listed. Certified to CAN/CSA/ANSI Standards. RoHS compliant. Title 24 and JA8 compliant (when using factory lamp options). Suitable for indoor or outdoor use and in wet locations. Made in the USA with sustainable processes.
INCLUDED ITEMS	Fixture, Mounting Stake	



**B-K LIGHTING**

**MADE IN THE USA**

559.438.5800 | [INFO@BKLIGHTING.COM](mailto:INFO@BKLIGHTING.COM) | [BKLIGHTING.COM](http://BKLIGHTING.COM)